MILESTONE CASEMENT SELECTION SHEET

Shaded cells indicate the default choice if no other selection is made

| UNIT: | □ Left Hinge □ Right Hinge □ Stationary (choose one) | | | |
|------------------------------|--|-----------------------------------|---------------------------|----------------|
| QUANTITY: | | | | |
| EXTERIOR: | □ Natural | □ Primed | □ Painted, Color: | □ Other: |
| INTERIOR: | □ Natural | □ Primed | □ Other | |
| GLAZING: | □ Regular Insulated | □ Low E – Argon | □ Low E – Krypton | □ Other |
| SPECIAL GLASS: | □Wavy Restoration | □ Tempered | □ Obscure | □ Other |
| LOCK: | □ Oil Rubbed Bronze | □ Other | | |
| DIVIDED LIGHT PATTERN: | □ 2w2h | □ 2w3h | □ 2w4h | □ 2w5h |
| | □ 2w6h | □ 3w2h | □ 3w3h | □ 3w4h |
| | □ 3w5h | □ 3w6h | □ Other | |
| DIVIDED LIGHT METHOD: | □ 5/8" SDL | □ 7/8" SDL | □ Full Surround Grille | □ Other |
| SPACER FOR DIVIDED LIGHT: | □ No | Yes □ Gray □ Black | | |
| JAMB DEPTH: | □ 4 9/16" | □ 6 9/16°° | □ Other | |
| EXTERIOR CASING: | □ None, Clad Unit Has Nailing Fin | □ None, 4" sill horns | □ Brickmold | □ 5/4 x 4 Flat |
| | □ 5/4 x 5 Flat | □ 5/4 x 6 Flat | □ No Finger Joints | □ Other |
| SPECIAL CASING DETAIL: | ☐ Flat Pediment Head Applied | ☐ Angled Pediment Head Applied | □ Other | |
| SILL: | □ Standard | □ Thick "Historic" | □ No Finger Joints | □ Other |
| SCREEN: | □ Wood Swing, Fiberglass Mesh | □ Wood Swing, Aluminum Mesh | □ Other | |